


279.00 EUR
incl. 19% VAT, plus [shipping](#)



- Intel® LGA1151 Socket Core i3, i5, i7 & Pentium Processors (max. 65W)
- Intel® H110 Express Chipset
- Support Dual Channel DDR4 2133MHz, 2 * DIMM slot, up to 32GB memory
- 2 * Realtek Gigabit LAN (RTL8111G)
- 3 * SATA III (6Gb/s), 1 * M.2 (M key 2242, 2260, 2280, 22110)
- 4 * USB 3.0, 5 * USB 2.0/1.1
- 10 * COM ports (COM1 supports RS232/422/485)
- Support TPM 1.2 function (option)
- Micro ATX form factor (244mm x 244mm)

Form Factor	
Dimensions	- Micro ATX (244 * 244mm)
Processor System	
CPU	- Intel LGA 1151 Socket Core i7 / i5 / i3 & Pentium Processors
Core Number	- (By CPU)
Max Speed	- (By CPU)
L2 Cache	- (By CPU)
Chipset	- Intel H110 Chipset
BIOS	- AMI 64Mb Flash ROM

Expansion Slot	
Mini-PCIe	- 1 (full size)
m.2	- 1 (M Key 2242, 2260, 2280, 22110)
PCIe	- 1 * PCIe x16 & 1 * PCIe x 1
PCI	- 2
SIM card holder	- 1
Memory	
Technology	- Dual Channel DDR4 2133MHz
Max.	- 32GB
Socket	- 2 * DIMM
Graphics	
Controller	- Intel® Gen9 Graphics supports DX 11/12, OGL4.3 / 4.4
VRAM	- Shared Memory
VGA	- 1 (Max. Resolution : 1920*1200@60Hz)
DVI-D	- 1 (Max. Resolution : 1920*1200@60Hz)
HDMI	- 1 (Max. Resolution : 3840*2160@24Hz)
DP	- 0
eDP	- 0
MultiDisplay	- Dual Display
Ethernet	
Ethernet	- 10/100/1000 Mbps
Controller	- PCIe GbE LAN : Realtek RTL8111G
Connector	- 2 * RJ 45
Audio	
CODEC	- HD Audio : Realtek ALC662
Channel	- 6 Channel