

918.00 EUR  
incl. 19% VAT, plus [shipping](#)



- INTEL® BayTrail--M N2930 SOC Chip
- Onboard INTEL® BayTrail-M N2930 1.83GHz Quad Cores CPU
- Onboard SAMSUNG 4G/1333MHz DDR3L Memory
- Support DirectX 11 3D Graphics Acceleration
- Support 1\*Serial ATAII(3Gb/s) Devices
- Support Dual INTEL® Gigabit LAN
- Support CRT Output
- Equipped with 802.11 b/g/n WIFI card & External Antenna
- Support 3\* COM ports■COM2/COM3 Support RS422/485■
- Support 2.5" SATA HDD
- Support 1\*M-SATA Socket
- Support 1\*Mini PCI-E Socket
- Support 3\* USB2.0 Ports
- Support 1\* USB3.0 Port
- Support 3G SIM Card
- Support slick design
- VESA mount(100mm X100mm &75mm x 75mm)

Panel

Panel Spec	AUO G104STN01.0
Viewable Size Image	10.4 inch With LED Backlight
Active Area	211.2(H) x 158.4(V)
Resolution	800 x 600 @60Hz
Display Color	262K
Pixel Pitch	0.264 x 0.264 mm
Aspect Ratio	4:3
Contrast Ratio	700:1
Max Brightness	400 cd/m <sup>2</sup>
Viewing Angle(H/V)	H160/V130
Response Time	10ms
Temperature Range	-30 ■ +80■(Operating)
Touch	
Touch panel style	5 wires analog resistive
Active Range	211.58 x 158.75mm ±0.2mm
Temperature Range	-10 ~ +60■(Operating)
Transparency	80 ±3%
Surface Hardness	■ 3H (ASTM D3363, pressure 750g/45°)
Operating Force	■ 80g
Knock test	10,000,000 times keystrokes
Case	
Panel Material	Aluminum
Case Material	Iron
Color	Black
Coating Requirement	Spray Paint
Protection grade■IP■	IP65
Speaker	N/A
Bracket	6 (Top:2pcs■Side:4pcs, Optional)
Installation Type	Open Frame / Wall Hanging■Optional■
Cooling Mode	Fan less Fully sealed design
System Specification	
Form Factor	4"
Processor	INTEL® BayTrail-M N2930 1.83GHz/QC
System Chipset	INTEL® BayTrail-M N2930 (SOC)
System Memory	4G/1333MHz DDR3L SAMSUNG DRAM
BIOS	64MB SPI Flash ROM
Ethernet	2*INTEL® I211AT Gigabit LAN
Audio	Realtek® ALC887 HD Audio
Storage	1* Serial ATA2 3Gb/s connector 1* M-SATA connector
WIFI Module	N/A(Optional)
Optical Device	N/A
Expansion	PCI-E mini card for WLAN
Display Output	CRT
I.O Port	1*USB3.0■3*USB2.0■1*RS232■ 2*RS232/422/485■1*Line-out
Power Adapter	DC-IN (9~24V,Euro terminal block)
OS Support	Windows 7/8/8.1
Temperature	Operating■-10 ~ +60■
Humidity	20%~90% (non condensing)
Shock	Operating■15G■11ms duration
Vibration	Operating■5~500Hz/1 Grms
Net Weight (kg)	
Dimension	284.0mm*230.0mm*37.0mm
Certification	FCC CE IP65

Other	Support Non wire I.O interface output
Other Information	
Application	Commercial ■ Banking ■ Digital Signage POS/KIOSK ■ Industrial Automation
Special Features	Metal design, compact ■ slick
Other	Optional wall hanging telescopic bracket, etc., can also be used as the embedded security
Accessory	
Adapter	1* 60W AC-DC Adapter
Power cord	1* Power cord
Manual	2* Manual
CD	1* CD
Other	2* WI-FI antenna