

369.00 EUR
incl. 19% VAT, plus [shipping](#)



Support:  [Specifications](#)

| | |
|---|--|
| Chip | IC+, Powerchip : Maxim |
| Dimensions | 440x200x44mm |
| Certifications&Safety | CE, FCC, ROHS |
| I/O Ports | 16x 10/100BaseT(X) 2x self-switching Gigabit ports LED: Power, port speed, port connection |
| Management | Support WEB Interface, Support SNMP v1/v2/v3 |
| Standards | IEEE802.3 10Base-T Ethernet standard IEEE802.3u 100Base-TX Fast Ethernet standard IEEE802.3x full duplex flow control and Backpressure half duplex flow control IEEE802.3ab 1000Base-T Ethernet standard IEEE802.3z Gigabit Ethernet (optical) IEEE802.3ab link aggregation |
| Network interface / Wire specifications | 10BASE-T: Category 3 and above non-mask / mask twisted pair (<=100 m) 100BASE-TX: Category 5 and above non-mask / mask twisted pair (<=100 m) 1000BASE-T: Category 5 and above non-mask / mask twisted pair (<=100 m) |
| PoE Support | PoE standard: IEEE802.3af, IEEE802.3at Each port provides 15.4W, maximum 30W Pin Definition: V+ (RJ45 Pin 1, 2), V- (RJ45 Pin 3, 6) PoE Management: Supports port-based PoE status display and PoE switch control |
| Power input / consumption | AC90-240V input, Built-in 270W open frame power supply |
| Operating temperature | 0~40°C |
| Cooling | Mute fan (4020) |
| MTBF | 100.000hrs |