





598.00 EUR incl. 19% VAT, plus shipping



- 7" 320 nits high brightness TFT LCD with LED backlight
- 10-points Multi Capacitive Touch
- Streamlined enclosure for highly efficient heat dissipation
- · Enclosed in robust aluminum casing
- Edge-to-edge narrow bezel design and Fanless cooling system
- Design for easy Wall mount, Panel Mount, VESA Mount installation
- A true Flat, easy-to-clean front surface with edge-to-edge design
- Front bezel meets IP65-rated protection

Jetway HPC070SC-FP2807A Flat-PanelFanless Panel PC provides outstanding outlook with industrial-grade quality for comprehensive industrial markets, such as retails, wholesales, hospitality, hospital or meeting room registration, logistics, self-service kiosk, residential automation and digital signage.

Jetway HPC070SC-FP2807A Flat-PanelFanless Panel PC is designed with 10-points Multi capacitive type touch screen. High brightness TFT LCD panel with LED backlight are equipped with this model. Streamlined enclosure with narrow bezel design.

Jetway HPC070SC-FP2807A Flat-Panel Fanless Panel PC are designed with a true flat, easy-to-clean front surface with edge-to-edge design. It is designed mounting clips for easy Wall mount, Panel Mount, VESA Mount installation.

Front bezel meets IP65-rated & NEMA 4 protection. Welcome to use Jetway Flat-Panel Panel PC.

Display	
Front Bezel	- IP65, NEMA 4 rugged protection, Full planar metal border



## Jetway HPC070SC-FP2807A Panel-PC (7" 1024x600 PCAP Touchscreen, Intel N2807, 2GB RAM) [IP65/NEMA4 Front]

[http://www.minipc.de/catalog/il/2352]

Display Color	Display Type	- 7" With LED Backlight
Page	Brightness (cd/m²)	- 320 nits
Viewing Angle (HIV)	Display Color	– 16.7M
Pixel Pitch	Resolution	- 1024 x 600 @ 60Hz
Appert Ratio	Viewing Angle (H/V)	- 150°/145°
Spring	Pixel Pitch	– 0.15 x 0.15 mm
Touch Screen	Aspect Ratio	<b>- 16:9</b>
Touch Screen	Contrast Ratio	- 500:1
Projected capacitive type	Response Time	- 30 ms
Active Range	Touch Screen	
Transparency = ■85%  Surface Hardness   ■86H (JIS-5400)  Glass haze value   ■ 3%  CASE  Value   Auminum   Octobro	Туре	- projected capacitive type
■6H (JIS-5400)	Active Range	- 152.40 x 91.44mm ±0.2mm
■ 3%	Transparency	- ■85%
CASE	Surface Hardness	– ■6H (JIS-5400)
Panel Material	Glass haze value	<b>-■</b> 3%
Case Material	CASE	
Silver + white	Panel Material	- Aluminum
Spray Paint	Case Material	– Iron
Main System	Color	- Silver + white
CPU	Coating Requirement	- Spray Paint
CPU	Main System	
BIOS	CPU	- Intel® Bay Trail-M N2807 1.58GHz/DC
Storage	RAM	– 2G 1333MHz DDR3L SAMSUNG DRAM
Variable	BIOS	- 64MB SPI Flash ROM
OS Support  - Windows 7 / 8.1 / 10 / Linux (Option)  I/O Connector  - 1 * USB3.0 - 1 * USB2.0 - 1 * RS232/422/485 - 1 * HDMI - 1 * LAN (Gigabit LAN) - 1 * Euro terminal block by 12V DC input - 1 * Power button  Expansion Interface  Expansion  - 1 * PCI-E mini card for WIFI or 3G/4G  Power  Power Input - Supports 12V DC Power in with over current protection fuse - Provides 100–240V AC-DC 12V, 60W power adapter  Power Consumption - 13W  Dimension  Case Dimensions - 197.0*136.0*50.7mm	Storage	- 1 * mSATA connector (Full size)
I/O Connector  I/O Ports and Switches  I/O Ports and S	Watchdog Timer	- 256 levels, 0~255 sec.
- 1 * USB3.0 - 1 * USB2.0 - 1 * RS232/422/485 - 1 * HDMI - 1 * LAN (Gigabit LAN) - 1 * Euro terminal block by 12V DC input - 1 * Power button  Expansion Interface  Expansion  - 1 * PCI-E mini card for WIFI or 3G/4G  Power  Power Input - Supports 12V DC Power in with over current protection fuse - Provides 100-240V AC-DC 12V, 60W power adapter  Power Consumption - 13W  Dimension  Case Dimensions - 197.0*136.0*50.7mm	OS Support	- Windows 7 / 8.1 / 10 / Linux (Option)
-1 * USB2.0	I/O Connector	
I/O Ports and Switches  - 1 * HDMI - 1 * LAN (Gigabit LAN) - 1 * Euro terminal block by 12V DC input - 1 * Power button  Expansion Interface  Expansion  - 1 * PCI-E mini card for WIFI or 3G/4G  Power  Power Input - Supports 12V DC Power in with over current protection fuse - Provides 100~240V AC-DC 12V, 60W power adapter  Power Consumption - 13W  Dimension  Case Dimensions - 197.0*136.0*50.7mm		
Expansion Interface  Expansion	I/O Ports and Switches	- 1 * HDMI - 1 * LAN (Gigabit LAN)
Expansion - 1 * PCI-E mini card for WIFI or 3G/4G  Power  Power Input - Supports 12V DC Power in with over current protection fuse - Provides 100~240V AC-DC 12V, 60W power adapter  Power Consumption - 13W  Dimension  Case Dimensions - 197.0*136.0*50.7mm  Certifications		
Power Input  - Supports 12V DC Power in with over current protection fuse - Provides 100~240V AC-DC 12V, 60W power adapter  Power Consumption  - 13W  Dimension  Case Dimensions  - 197.0*136.0*50.7mm  Certifications	•	4 * DOLE mini and for WIEL or 20 /40
Power Input  - Supports 12V DC Power in with over current protection fuse - Provides 100~240V AC-DC 12V, 60W power adapter  Power Consumption  - 13W  Dimension  Case Dimensions  - 197.0*136.0*50.7mm  Certifications		- I POI-E MINI CARO TOF WIFT OF 3G/4G
Power Input - Provides 100~240V AC-DC 12V, 60W power adapter  Power Consumption - 13W  Dimension  Case Dimensions - 197.0*136.0*50.7mm  Certifications	Power	
Dimension  Case Dimensions - 197.0*136.0*50.7mm  Certifications	Power Input	- Provides 100~240V AC-DC 12V, 60W power adapter
Case Dimensions - 197.0*136.0*50.7mm  Certifications		- 13W
Certifications	Dimension	
	Case Dimensions	- 197.0*136.0*50.7mm
	Certifications	
Certifications – CE, FCC, IP65(Front)	Certifications	- CE, FCC, IP65(Front)
Environment	Environment	



## Jetway HPC070SC-FP2807A Panel-PC (7" 1024x600 PCAP Touchscreen, Intel N2807, 2GB RAM) [IP65/NEMA4 Front]

[http://www.minipc.de/catalog/il/2352]

Temperature	<ul> <li>Operating Temperature: -10 ~ 60° C (with W.T. DRAM/HDD in airflow condition)</li> <li>Storage Temperature: -20 ~ 85° C</li> </ul>
Shock	<ul><li>Operating: 15G■11ms duration</li></ul>
Vibration	- Operating: 5~500Hz/1 Grms
Warranty	
Warranty	- 2 Years Limited Warranty(Panel and Touch is only Warranty 1 Year)