





598.00 EUR incl. 19% VAT, plus shipping



- 8" 400 nits high brightness TFT LCD with LED backlight
- 10-points Multi Capacitive Touch
- Streamlined enclosure for highly efficient heat dissipation
- · Enclosed in robust aluminum casings
- Edge-to-edge narrow bezel design and Fanless cooling system
- Design for easy Wall mount, Panel Mount, VESA Mount installation
- A true Flat, easy-to-clean front surface with edge-to-edge design
- · Front IP65 for protection against water and dust

Jetway HPC080SC-FP2807A Flat-Panel Fanless Panel PC provides outstanding outlook with industrial-grade quality for comprehensive industrial markets, such as retails, wholesales, hospitality, hospital or meeting room registration, logistics, self-service kiosk, residential automation and digital signage.

Jetway HPC080SC-FP2807A Flat-Panel Fanless Panel PC is designed with 10-points Multi capacitive type touch screen. High brightness TFT LCD panel with LED backlight are equipped with this model. Streamlined enclosure with narrow bezel design.

Jetway HPC080SC-FP2807A Flat-Panel Fanless Panel PC is designed with a true flat, easy-to-clean front surface with edge-to-edge design. It is designed mounting clips for easy Wall mount, Panel Mount, VESA Mount installation.

Front bezel meets IP65-rated & NEMA 4 protection. Welcome to use Jetway Flat-Panel Panel PC.

Display	
Front Bezel	- IP65, NEMA 4 rugged protection, Full planar metal border
Display Type	- 8" With LED Backlight



Jetway HPC080SC-FP2807A Panel-PC (8" 1024x768 PCAP Touchscreen, Intel N2807, 2GB RAM) [IP65/NEMA4 Front]

[http://www.minipc.de/catalog/il/2353]

Certifications Certifications Environment	– CE, FCC, IP65(Front)
	_ CE_ECC_IP65/Eront\
Cartifications	
	3.135 135.5 1 3.11 3.11.11
Case Dimensions	- 191.05*150.54*57.70mm
Dimension	
Power Consumption	- 13W
Power Input	 Supports 12V DC Power in with over current protection fuse Provides 100~240V AC-DC 12V, 60W power adapter
Power	
Expansion	- 1 * PCI-E mini card for WIFI or 3G/4G
Expansion Interface	
	- 1 * Power button
	- 1 * Euro terminal block by 12V DC input
	- 1 * LAN (Gigabit LAN)
I/O Ports and Switches	– 1 * HDMI
	- 1 * RS232/422/485
	- 1 * R\$232
	- 1 * USB3.0 - 3 * USB2.0
I/O Connector	4.4.11000.0
OS Support	- Windows 7 / 8.1 / 10 / Linux (Option)
Watchdog Timer	- 256 levels, 0~255 sec.
Storage	- 1 * mSATA connector (Full size)
	- 64MB SPI Flash ROM
BIOS	
RAM	- Intel® Bay Trail-M N2807 1.58GHz/DC - 2G 1333MHz DDR3L SAMSUNG DRAM
Main System CPU	– Intel® Bay Trail-M N2807 1.58GHz/DC
	opidy i dilik
Coating Requirement	- Spray Paint
Color	- Silver + white
Case Material	– Iron
Panel Material	— Aluminum
CASE	
Glass haze value	_ ■ 3%
Surface Hardness	– ■6H (JIS-5400)
Transparency	
Active Range	- 163.05 x 122.54mm ±0.2mm
Туре	- projected capacitive type
Touch Screen	
Response Time	- 30 ms
Contrast Ratio	
Aspect Ratio	
Pixel Pitch	– 0.158 x 0.158 mm
Viewing Angle (H/V)	
Resolution	– 1024 x 768 @ 60Hz
Display Color	
Brightness (cd/m²)	– 400 nits



Jetway HPC080SC-FP2807A Panel-PC (8" 1024x768 PCAP Touchscreen, Intel N2807, 2GB RAM) [IP65/NEMA4 Front]

[http://www.minipc.de/catalog/il/2353]

Temperature	Operating Temperature: -10 ~ 60° C (with W.T. DRAM/HDD in airflow condition) Storage Temperature: -20 ~ 85° C	
Shock	– Operating: 15G■11ms duration	
Vibration	- Operating: 5~500Hz/1 Grms	
Warranty		
Warranty	- 2 Years Limited Warranty(Panel and Touch is only Warranty 1 Year)	