



1449.00 EUR  
 incl. 19% VAT, plus [shipping](#)

- 1366x768 Multi-Touchscreen !
- Fanless ! IP65 Front !
- Intel Kaby Lake CPU !
- 2x LAN, 2x COM !



Support: [Specifications](#)

D151 series is a 15.6" ultra-thin wide-screen fanless Panel PC featuring Intel Kaby Lake ULV Core-i CPU. The distinct aluminum extrusion frame with matte black or silver finish gives the system an understated luxury and elegant look. The series also featuring a bright TFT-LCD with LED backlight display and true flat 10-point projective capacitive multi-touch front panel that's IP65 compliant, along with optional universal snap-in peripherals (MSR, Smart card reader, NFC/ RFID reader, barcode scanner, camera), making it perfect for diversified self-service and interactive signage markets including retail, hospitality, gaming, corporate, healthcare and light

industrial applications.

Model Name	D151-11KS
Motherboard	PD11KS
Processor	Intel Kaby Lake-U i3-7100U with integrated graphics (Compatible with Skylake 3955U / i3-6100U / i5-6300U / i7-6600U and KabyLake 3965U / i5-7300U / i7-7600U)
System Memory	2 x DDR4 SO-DIMM, support up to 32GB
Processor Graphic	Intel® HD Graphics 620 (Graphics Burst Frequency 1.10GHz)
Touch Display	
LCD Size	15.6" TFT LCD with LED Backlight 50000 lifetime
Brightness	500nits
Resolution	1366 x 768
Viewing Angle	170°/160°
Touch Screen	True-flat 10 points projective capacitive touch
Storage	
HDD/SSD	1 x 2.5 internal HDD/SSD bay
Expansion	
Extension slots	M.2 (2230) : 1 x M.2 E key for wireless network MiniPCIe : 1 x full length mPCIe supporting mSATA
I/O Ports	
DC Jack	1 (8V to 24V wide-range voltage input)
USB3.0	4
GigaLAN (10/100/1000)	2
Display-Port (support 4K 3840x2160)	1
Audio jack	1 x combo jack w/mic-in and line-out
HDMI-out	1
Serial Port	1 x RS-232, 1 x RS-232/422/485
Thermal Solution	
Thermal Solution	Fanless
Audio	
Stereo Speaker	2W x 2
Power	
Power Supply	65W/19V
Certification	
EMC & Safety	CE/FCC Class A
Environment	
Operating Temperature	0°C ~ 40°C (32°F~104°F)
Storage Temperature	-20°C ~ 60°C(-4°F~140°F)
Relative Humidity	10%~95% @40°C non-condensing
Front Panel Protection	IP65 Compliant
Dimension	400 x 250 x 44 (mm)
Weight	4.8kg (10.58 lb)
Mounting	100mm x 100mm VESA
Operating System	win10, linux support by request