

698.00 EUR  
incl. 19% VAT, plus [shipping](#)



- INTEL® LGA 1151 Socket Core™ i3, i5, i7 & Pentium Processors
- INTEL® Q170 Express Chipset
- DDR4-2133MHz / SO-DIMM \*2 / Max : 32GB
- Giga LAN Port \* 2 (INI219LM + i211AT)
- Support DVI-I Port \* 1, HDMI \* 1, DP \* 1
- Support COM Port \* 2 (1\*RS232 ,1\* RS232/422/485 )
- Support USB 3.0 Port \* 6
- Applications ■ Industrial Control System, Networking Server System, Workstation

• Product Dimension	• 430 (W) * 250 (D) * 44 (H) mm
• Product Model	• JBC150F594-Q170-B
• MB Model & Size	• NF594-Q170 (Mini-ITX)
• CPU	• Intel LGA 1151 Socket Core™ i3, i5, i7 & Pentium Processors
• Chipset	• Intel® Q170 Express Chipset
• Memory	• DDR4-2133MHz / SO-DIMM *2 / Max : 32GB
• Specs Devices	• 3.5" SATA Device * 1 or 2.5" SATA Device * 2
• Colors	• Black
• Front I/O Port	• Power SW * 1 • Reset SW * 1 • Power LED * 1 • HDD R/W LED * 1 • USB 2.0 * 2
• Rear I/O Port	• Power SW * 1 , Reset SW * 1 • Power LED * 1 , HDD R/W LED * 1 • Intel Giga LAN Port * 2 (INI219LM + i211AT) • DVI-I Port * 1, HDMI * 1, DP * 1 • COM Port * 2 (1*RS232 ,1* RS232/422/485 ) • USB 3.0 Port * 6 • MIC * 1, Line in * 1, Line out * 1 • AC Input * 1
• PSU	• 1U-200W / Support PFC / 150 (L) *81.5 (W) *40.5 (H) mm (FLEX)
• FAN	• 4020 FAN * 3 / 7000 rpm / DC-12V-0.1A / 8 CFM
• Expansion	• PCI-E x 16 Slot * 1
• Storage	• 3.5" HDD * 1 or 2.5" HDD * 2 (Support SATA 3 )
• Accessory	• Power cord * 1 • Quick Installation Guide * 1 • User Manual * 1 • CD * 1 • Screw Package * 1

<ul style="list-style-type: none"> <li>Packing</li> </ul>	<ul style="list-style-type: none"> <li>Net Weight■3.5KG</li> <li>Gross Weight■4.5KG</li> <li>Color Box Dimension■530 (W) x 352 (D) x 142 (H) mm</li> </ul>
<ul style="list-style-type: none"> <li>Certification</li> </ul>	<ul style="list-style-type: none"> <li>CE , FCC , RoHS , REACH</li> </ul>
<ul style="list-style-type: none"> <li>Applications</li> </ul>	<ul style="list-style-type: none"> <li>Industrial Control System</li> <li>Networking Server System</li> <li>Workstation</li> </ul>