



489.00 EUR
incl. 19% VAT, plus [shipping](#)



- Intel® Apollo Lake SoC Processor
- 1 * DDR3L SODIMM Up to 8GB
- 4 * COM, 4 * USB3.0, 1 * HDMI, 1 * DP, 1 * RJ45, 1 * MIC, 1 * Line-in, 1 * Line-out
- M/B Form Factor : Mini ITX (170x170mm)
- 1U 200W FLEX Power

MB Model	<ul style="list-style-type: none"> - JNF694L-3350 / Mini ITX - JNF694L-4200 / Mini ITX
Part No.	<ul style="list-style-type: none"> - HBJC143F694-335B (non-WIFI) / HBJC143F694W-335B (WIFI) - HBJC143F694-420B (non-WIFI) / HBJC143F694W-420B (WIFI)
BIOS	- AMI Flash ROM
CPU/Chipset	- INTEL® Apollo Lake SoC Processor
Memory	- 1 * DDR3L-1866 MHz up to 8 GB
Storage	<ul style="list-style-type: none"> - 1 * 2.5" SATA 6Gb/s_ internal drive bay - 1 * M.2_SSD (M key-2242/2260)
Network	<ul style="list-style-type: none"> - 1 * Realtek® 8111H Gigabit LAN - 1 * Full-size mini-PCIE slot (802.11 b/g/n + BT 4.0 installed in WIFI model / Optional)
Rear Panel I/O	<ul style="list-style-type: none"> - 4 * USB 3.0 - 1 * HDMI 1.4 (Max Resolution : 3840x2160@24Hz) - 1 * DP (Max Resolution : 4096x2160@60Hz) - 1 * RJ45 - 1 * MIC, 1 * Line-in , 1 * Line-out (Realtek ALC662) - 4 * RS232 - 1 * AC-in CON
Front Panel I/O	<ul style="list-style-type: none"> - 1 * Power button, 1 * Reset button - 1 * Power LED, 1 * HDD LED - 2 * USB 2.0
Power Source	<ul style="list-style-type: none"> - 1U 200W FLEX POWER - AC 90~240V input
Compliance	- CE, FCC, RoHS
Temperature	<ul style="list-style-type: none"> - Operating Temperature: 0 ~ 50° C - Storage Temperature: -10 ~ 70° C
Dimensions	- 330 (W) x 192 (D) x 44 (H) mm
Packing	<ul style="list-style-type: none"> - Net Weight: 3.5KG - Gross Weight: 4.5KG - Color Box dimension: 406 (W) * 359 (D) * 148 (H) mm
OS Support	- Windows 10 64bit, latest Linux kernel

Warranty	- 2 Year limited warranty
----------	---------------------------