

579.00 EUR
incl. 19% VAT, plus [shipping](#)

Jetway HPC080SC-FP3350 Flat-Panel Fanless Panel PC provides outstanding outlook with industrial-grade quality for comprehensive industrial markets, such as retails, wholesales, hospitality, hospital or meeting room registration, logistics, self-service kiosk, residential automation and digital signage.

Jetway HPC080SC-FP3350 Flat-Panel Fanless Panel PC is designed with 10-points Multi Capacitive Touch/Anti-Reflection Protection Glass type touch screen. High brightness TFT LCD panel with LED backlight are equipped with this model. Streamlined enclosure with narrow bezel design.

Jetway HPC080SC-FP3350 Flat-Panel Fanless Panel PC is designed with a true flat, easy-to-clean front surface with edge-to-edge design. It is designed mounting clips for easy Wall mount, Panel Mount, VESA Mount installation.

Front bezel meets IP65-rated & NEMA 4 protection. Welcome to use Jetway Flat-Panel Panel PC.

- 8.0" 400 nits high brightness TFT LCD with LED backlight
- 10-points Multi Capacitive Touch
- Enclosed in robust aluminum casings
- A true Flat, easy-to-clean front surface with edge-to-edge design
- USB3.0 Support Lock Device
- Front IP65 for protection against water and dust
- 12V DC-input Support, with EOS, OVP design

Display	<ul style="list-style-type: none"> - IP65, NEMA 4 rugged protection, metal front bezel - 8.0" With LED Backlight - 400 nits - 16.7M display color - 1024 x 768 @60Hz resolution - 160°/160° viewing angle (H/V) - 0.158 x 0.158mm pixel pitch - 4:3 aspect ratio - 700:1 contrast ratio - 30ms response time
Touch Screen	<ul style="list-style-type: none"> - Projected capacitive type - 163.05 x 122.54mm ±0.2mm active range - Transparency ■ 85% - Operating force ■ 50g - Surface Hardness ■ 6H (JIS-5400) - Glass haze value■ 3%
Case	<ul style="list-style-type: none"> - Aluminum panel - Iron case - Silver + white color - Spray paint coating requirement
Main System	<ul style="list-style-type: none"> - Intel® Apollo Lake N3350 1.1GHz/DC processor - 1* DDR3L SO-DIMM (Max 8GB) - 128MB SPI Flash ROM - Watchdog Timer 256 levels, 0~255 sec. - OS Support Windows 10 / Linux
Storage	<ul style="list-style-type: none"> - 1* M.2 Socket (2242 size)
Expansion	<ul style="list-style-type: none"> - 1* Mini PCIe for WIFI or 3G/4G
I/O Connector	<ul style="list-style-type: none"> - 2* USB3.0 - 1* RS232/422/485 + 1* RS232 - 1* HDMI - 1* Realtek® RTL8111H GbE - 1* Locking Jack 12V DC input - 1* SIM card slot - 1* Power button
Power Input	<ul style="list-style-type: none"> - AC version: 100~240V AC-DC 60W power adapter or - DC version: 12VDC with over current protection fuse
Power Consumption	<ul style="list-style-type: none"> - 13W
Dimensions	<ul style="list-style-type: none"> - 199.05 * 158.54 * 57.70mm
Compliance	<ul style="list-style-type: none"> - CE, FCC, IP65(Front)-Option
Safety	<ul style="list-style-type: none"> - Shock: 11ms duration - Vibration: 5~500Hz/1 Grms
Temperature	<ul style="list-style-type: none"> - Operating: -10°C ~ 60°C - Storage: -20°C ~ 70°C
Warranty	<ul style="list-style-type: none"> - 2 Years Limited Warranty (Panel and Touch are only 1 Year Warranty)