

[http://www.minipc.de/catalog/il/2744]



579.00 EUR incl. 19% VAT, plus shipping

Jetway HPC080SC-FP3350 Flat-Panel Fanless Panel PC provides outstanding outlook with industrial-grade quality for comprehensive industrial markets, such as retails, wholesales, hospitality, hospital or meeting room registration, logistics, self-service kiosk, residential automation and digital signage.

Jetway HPC080SC-FP3350 Flat-PanelFanless Panel PC is designed with 10-points Multi Capacitive Touch/Anti-Reflection Protection Glass type touch screen. High brightness TFT LCD panel with LED backlight are equipped with this model. Streamlined enclosure with narrow bezel design.

Jetway HPC080SC-FP3350 Flat-Panel Fanless Panel PC is designed with a true flat, easy-to-clean front surface with edge-to-edge design. It is designed mounting clips for easy Wall mount, Panel Mount, VESA Mount installation.

Front bezel meets IP65-rated & NEMA 4 protection. Welcome to use Jetway Flat-Panel PC.

- 8.0" 400 nits high brightness TFT LCD with LED backlight
- 10-points Multi Capacitive Touch
- Enclosed in robust aluminum casings
- A true Flat, easy-to-clean front surface with edge-to-edge design
- USB3.0 Support Lock Device
- Front IP65 for protection against water and dus
- 12V DC-input Support, with EOS, OVP design



	The state of the s
Warranty	Storage: -20°C ~ 70°C2 Years Limited Warranty (Panel and Touch are only 1 Year Warranty)
Safety Temperature	− Operating: -10°C ~ 60°C
	– Vibration: 5~500Hz/1 Grms
0.6.6	– Shock: 11ms duration
Compliance	– CE, FCC, IP65(Front)-Option
Dimensions	- 199.05 * 158.54 * 57.70mm
Power Consumption	– 13W
Power Input	AC version: 100~240V AC-DC 60W power adapter orDC version: 12VDC with over current protection fuse
	- 1* Power button
I/O Connector	- 1* SIM card slot
	- 1* Locking Jack 12V DC input
	- 1* Realtek® RTL8111H GbE
	– 1* HDMI
	- 2 USB3.0 - 1* RS232/422/485 + 1* RS232
	- 2* USB3.0
Expansion	- 1* Mini PCle for WIFI or 3G/4G
Storage	- 1* M.2 Socket (2242 size)
	- OS Support Windows 10 / Linux
Main System	– Watchdog Timer 256 levels, 0~255 sec.
	– 128MB SPI Flash ROM
Case	- 1* DDR3L SO-DIMM (Max 8GB))
	- Intel® Apollo Lake N3350 1.1GHz/DC processor
	Spray paint coating requirement
	- Silver + white color
Touch Screen	Aluminum panel Iron case
	- Glass haze value■ 3%
	- Surface Hardness ■ 6H (JIS-5400)
	- Transparency ■ 65% - Operating force ■ 50g
	– 163.05 x 122.54mm ±0.2mm active range– Transparency ■ 85%
Display	- Projected capacitive type
	- 30ms response time
	- 700:1 contrast ratio
	- 4:3 aspect ratio
	– 0.158 x 0.158mm pixel pitch
	- 160°/160° viewing angle (H/V)
	– 1024 x 768 @60Hz resolution
	- 16.7M display color
	– 400 nits
	- 8.0" With LED Backlight
	- IP65, NEMA 4 rugged protection, metal front bezel