



609.00 EUR

incl. 19% VAT, plus [shipping](#)

- 9-36V DC-in !
- ARM Cortex RK3288 !
- Android 5.1/9.0, Debian 9.0 !
- IP65 Front !

- 13.3" 350 nits TFT LCD with LED backlight
- ARM Cortex RK3288 CPU, 4x 1,8 GHz
- Onboard 1333/2GB DDR3L DRAM
- Onboard 8G Flash ROM
- Support Android 5.1/9.0 or Debian 9.0

- Front IP65 for protection against water and dust
- Support 9-36V DC-in

Display	<ul style="list-style-type: none"> - IP65, NEMA 4 rugged protection, metal front bezel - 13.3" With LED Backlight - 300 nits Brightness (cd/m²) - 262K display color - 1920 x 1080 @ 60Hz resolution - 170°/170° viewing angle (H/V) - 0.153 x 0.153mm pixel pitch - 16:10 aspect ratio - 600:1 contrast ratio - 35ms response time
Touch Screen	<ul style="list-style-type: none"> - Projected capacitive type - 355.0 x 197.0mm ±0.3mm active range - Transparency ■ 85% - Operating force ■ 50g - Surface Hardness ■ 6H (ASTM D3363, pressure 1N/45°)
Case	<ul style="list-style-type: none"> - Aluminum panel - Iron case - Black color - Spray paint coating requirement
Main System	<ul style="list-style-type: none"> - Rockchip® ARM Cortex A17 1.8GHz/QC processor - Onboard 1333/2GB DDR3L DRAM - Onboard 8G Flash ROM - Watchdog Timer 256 levels, 0~255 sec. - Speaker: 2* 2W/8Ohm - Camera: 1* 500W USB (Option) - OS Support Android 5.1/9.0 or Debian 9.0 - Power Consumption: 12.5W
Expansion	<ul style="list-style-type: none"> - 1* Micro SD socket
I/O Connector	<ul style="list-style-type: none"> - 2* USB2.0 (USB1 Co-lay OTG) - 1* HDMI 1.4 - 1* AUDIO(Line-out +MIC) - 1* Micro SD Socket - 1* Power Button - 1* GbE - 1* 9~36V DC jack
Power Input	<ul style="list-style-type: none"> - 9~36V DC-in
Dimensions	<ul style="list-style-type: none"> - 337.8 * 211.4 * 39.0mm
Compliance	<ul style="list-style-type: none"> - CE, FCC, IP65(Front)-Option
Safety	<ul style="list-style-type: none"> - Shock: 15G, 11ms duration - Vibration: 5~500Hz/1 Grms
Temperature	<ul style="list-style-type: none"> - Operating: -10°C ~ 50°C - Storage: -20°C ~ 60°C