

759.00 EUR
 incl. 19% VAT, plus [shipping](#)

- Tiger Lake-UP3 SoC !
- TDP 15W !
- 2* HDMI, 2* DP !



- Intel® Tiger Lake-UP3 SoC Processor (TDP 15W)
- 2* DDR4 3200MHz SO-DIMM up to 64GB
- 2* Intel GbE
- 1* M.2 M-key 2242/2280, 1* M.2 E-key 2230 Support CNVi, 1* M.2 B-key 3042/3052
- 2* HDMI, 2* DP
- Support Fanless cooling design

MB Model	– JMU10-1135G7 – JMU10-1145G7 (Default)	
Part No	Non-Wifi	M.2 ac WiFi card
	– HBJC330U10-1135G7 – HBJC330U10-1145G7	– HBJC330U10I-1135G7 – HBJC330U10I-1145G7
BIOS	– AMI SMT Flash ROM	
Processor	– Intel® Tiger Lake-UP3 Processor (TDP 15W), Default: 1145G7E Notes: When the system runs, CPU will automatically adjust its working clock frequency according to changing workload.	
Network	– 2* Intel® GbE – 1* M.2 E-Key 2230 for WiFi support CNVi – 1* M.2 B-Key 3042/3052 for 4G/5G module	
Memory	– 2* DDR4 3200MHz SO-DIMM up to 64GB	
Storage	– 1* M.2 M-key 2242/2280 (PCIe4.0 x4/SATAIII interface) support NVMe – 1* SATAIII (SATA PWR support 5V only)	

Expansion slot	<ul style="list-style-type: none"> - 2 * Mini PCIe (full-size, for WiFi & CAN BUS expansion) - 1 * Mini PCIe slot (only USB signal, full-size, for 4G LTE + GPS expansion)
Rear Panel I/O	<ul style="list-style-type: none"> - 2* USB3.2 / C Type (Support DP1.4) - 1* SIM Card slot - 2* HDMI - 2* RJ45 - 1* DC Jack
Front Panel I/O	<ul style="list-style-type: none"> - 1* Audio Jack (Line out +MIC) - 2* USB3.2 / A Type - 1* USB3.2 / C Type - 1* Power Button + Led
Compliance	- CE, FCC, RoHS, ErP Ready (Option)
Power Source	<ul style="list-style-type: none"> - Adapter : DC12V_5A_60W - M/B: DC 12~24V input
Safety	- CE, FCC, LVD, RoHS
Temperature	<ul style="list-style-type: none"> - Operating Temperature: -10 ~ 50° C - Storage Temperature: -20 ~ 60° C
Dimensions	- 150.0 (W) x 109.2 (D) x 75.0 (H) mm
OS Support	- Windows 10, Linux
Warranty	- 2 Year limited warranty