

469.00 EUR  
 incl. 19% VAT, plus [shipping](#)



- Intel Bay Trail !
- -40 - 70°C !
- 9-24V DC !
- All-aluminium !

Support: [Datasheet](#)

- Intel® Bay Trail SoC Processor (Default: J1900)
- Support 1 \* SO-DIMM DDR3L-1333MHz up to 8GB
- All-aluminum body, produced by casting process
- Operating Temperature: -40 ~ 70° C
- 9~24V DC-in (Lockable type)

MB Model	- MZ93-00B
Part No.	- HBJC386Z9300-J19B - HBJC386Z9300J-J19B (support M.2 ac WiFi)
BIOS	- AMI Flash ROM
CPU/Chipset	- Intel® Bay Trail SoC Processor (Default: J1900)
Memory	- Support 1 * SO-DIMM slots DDR3L-1333MHz up to 8GB
Network	- 2 * Intel i211-IT GbE
Storage	- 1 * M.2 M-key 2242/2280 slot (M2M, support SATA interface)
Expansion	- 1 * M.2 E-key 2230 (M2E, support USB 2.0/PCIex1 interface) - 1 * M.2 B-key 3042 slot (M2B, support USB 3.0 interface)
Rear Panel I/O	- 2 * RJ45 - 1 * DVI-I (Max. Resolution: 1920 * 1200@60Hz) - 1 * HDMI (Max. Resolution: 1920 * 1200@60Hz) - 1 * 8 bit GPIO - 1 * Line out & MIC combo - 1 * DC-in (Lockable type)

Front Panel I/O	<ul style="list-style-type: none"> <li>- 1 * Power SW + Power LED</li> <li>- 1 * HDD LED , 2 * LAN LED</li> <li>- 1 * SIM Card slot</li> <li>- 4 * COM (COM1_support RS485)</li> <li>- 4 * USB2.0</li> <li>- 2 * USB3.0</li> </ul>
Power Source	<ul style="list-style-type: none"> <li>- Adapter / AC 90~240V input / DC12V-60W</li> <li>- MB : support DC 9~24V input</li> </ul>
Compliance	<ul style="list-style-type: none"> <li>- CE, FCC, LVD, RoHS, ErP Ready</li> </ul>
Temperature	<ul style="list-style-type: none"> <li>- Operating Temperature: -40 ~ 70° C (Under the condition of using M.2 interface SSD) (The test environment is closed and windless)</li> <li>- Storage Temperature: -40 ~ 80° C</li> <li>- Humidity : 10% ~ 90% RH @40°C (non-condensing)</li> </ul>
Dimensions	<ul style="list-style-type: none"> <li>- 185 (W) x 142 (D) x 60 (H) mm</li> </ul>
OS Support	<ul style="list-style-type: none"> <li>- Windows 10, Linux</li> </ul>