



98.95 EUR incl. 19% VAT, plus shipping

- I2C!
- MCP23008!

Expansion Module Adding functions for controllers NORVI is always about on connectivity and expandability. This is the time to make use of Expansion port of NORVI Controllers. The series of expansion modules connects to NORVI IoT controllers via its I2C and UART connections. You can add more features to the NORVI Controller without huge customizations. NORVI provides true technology with reliability for industrial applications being worlds iot hardware manufacturer. We have included NB-IoT, LoRa and analog modules as expansions.

- Normally Open Relay Outputs
- Loads upto 5 A 30 VDC/250 VAC resistive
- MCP23008 Port Expander
- Address Configurable Over DIP Switch
- 8 x Relay Outputs

Product Specification	
Range of product	NORVI EX
Product type	I/O Expansion Module
Rated supply voltage	24V DC
Discrete input number	8 x Relay Outputs / NORVI-EX-R8
Communication	12C
Main	
Supply voltage limits	20.428.8V
Inrush current	<=10A



	1/8 HP 125 VAC/250 VAC
Relay Contact Rating	5 A 30 VDC/250 VAC resistive
	Pilot duty C 300
Local signaling	1 LED green for PWR
Electrical connection	Removable screw terminal block for inputs and outputs
	(pitch 5.08 mm)
Mounting support	Top hat type TH35-15 rail conforming to IEC 60715
	Top hat type TH35-7.5 rail conforming to IEC 60715
	Plate or panel with fixing kit
Height	90.50 mm
Depth	56.60 mm
VVidth	36.30 mm
Product weight	0.13 Kg
Environment	
Resistance to electrostatic discharge	4kV on contact
	8kV on air
Resistance to electro magnetic fields	10 V/m (80 MHz 1GHz)
	3 V/m (1.4 MHz 2 GHz)
	1 V/m (2 MHz 3 GHz)
Immunity to microbreaks	10 ms
Relative humidity	1095% without condensation in operation
IP degree of protection	IP20
Operating altitude	02000m
Operating Temperature	-40°C to +125°C
Storage altitude	03000m
Shock resistance	Storage altitude