

649.00 EUR

 incl. 19% VAT, plus [shipping](#)


- LGA1700 !
- H610 Chipset !
- 2x LAN !!
- 2x COM !

- Intel® 12/13th LGA1700 Socket Processor (Max. 65W TDPs)
- Intel® H610 Chipset
- 2\* DDR5 4800MHz SO-DIMM up to 64GB
- 8\* USB, 2\* RJ45, 1\* MIC, 1\* Line-out, 1\* Line-in, 2\* COM, 1\* DP, 1\* HDMI, 1\* VGA
- Onboard TPM2.0 (optional)

Model	– HBJC150I225-Q670B – HBJC150I225-H610B	
MB Model	– MI225Q6700 – MI225H6100	
CPU/Chipset	– Intel® 12th/13th LGA1700 Socket Core i7/i5/i3/Pentium/Celeron Processor (Max. 65W TDPs under 180A) – Intel® H610 Express Chipset	
BIOS	– AMI Flash ROM	
Memory	– 2* Dual CH non-ECC DDR5 4800MHz SDRAM SO-DIMM up to 64GB	
Network	– HBJC150I225-Q670: 1* Intel® i219-LM GbE + 1* Intel® i225-V 2.5GbE – HBJC150I225-H610: 1* Intel® i219-V GbE + 1* Intel® i225-V 2.5GbE	
Graphics	– Intel® UHD Graphics, shared memory – 1* DP 1.4a (Max Resolution: 4096x2304@60Hz) – 1* HDMI 2.0b (Max Resolution: 4096x2160@60Hz) – 1* VGA (Max Resolution: 1920x1080@60Hz)	
Storage	– 2* SATAIII (6 Gb/s) 2.5" Device , support RAID 0, 1 – 1* M.2 M-Key (2280, PCIe Gen.3 x4 interface) support NVMe – 1* M.2 M-Key (2242, PCIe Gen.4 x4/SATA interface) support NVMe (HBJC150I225-Q670 only)	
Expansion	– 1* M.2 E-Key (2230, USB2.0/PCIe Gen.3 x1 interface) support CNVi – 1* M.2 B-key (3042, PCIe Gen.3 x1/USB3.2 Gen.2/USB2.0 interface) (HBJC150I225-Q670 only) – 1* M.2 B-key (3042, PCIe Gen.3 x1 interface) (HBJC150I225-H610 only) – 1* PCIe Gen.4 x16	

Rear Panel I/O	<ul style="list-style-type: none"> <li>- 2* RJ45</li> <li>- 6* USB3.2(Gen.2) (HBJC150I225-Q670)</li> <li>- 4* USB3.2(Gen.2) + 2* USB2.0 (HBJC150I225-H610)</li> <li>- 1* HDMI</li> <li>- 1* DP</li> <li>- 1* VGA</li> <li>- 2* COM</li> <li>- 1* Audio (Line-in, Line-out, MIC)</li> </ul>
Front Panel I/O	<ul style="list-style-type: none"> <li>- 1* Power button, 1* Reset button</li> <li>- 2* USB2.0</li> <li>- 1* Power LED, 1* HDD LED</li> </ul>
Internal Connector	<ul style="list-style-type: none"> <li>- SIM Card slot</li> <li>- 1* GPIO (8 bit)</li> <li>- TPM2.0 (optional)</li> </ul>
Power Source	<ul style="list-style-type: none"> <li>- 1U FLEX 300W ATX PWR (4+24 pin)</li> </ul>
Compliance	<ul style="list-style-type: none"> <li>- CE, FCC, LVD, RoHS, ErP Ready</li> </ul>
Dimensions	<ul style="list-style-type: none"> <li>- Operating Temperature: 0 ~ 50° C</li> <li>- Storage Temperature: -40 ~ 85° C</li> <li>- Humidity: 10% ~ 95% RH @40°C (non-condensing)</li> </ul>
Temperature	<ul style="list-style-type: none"> <li>- Operating Temperature: 0 ~ 50° C</li> <li>- Storage Temperature: -40 ~ 85° C</li> <li>- Humidity: 10%~95% @40° C (non-condensing)</li> </ul>
OS Support	<ul style="list-style-type: none"> <li>- Windows 11, Linux</li> </ul>