

698.00 EUR
 incl. 19% VAT, plus [shipping](#)

- I5-10210U !
- 4x COM !
- 2x LAN !



- Intel® Whiskey Lake-U Processor
- 2* SO-DIMM DDR4-2400MHz up to 64GB
- 2* USB2.0, 4* USB3.1, 1* USB Type-C, 1* HDMI, 1* DP, 2* RJ45
- Support Max. 4K display resolution
- Adapter DC12V/90W

Model	– HBFDF835-8365-V (CPU: I5-8365UE, Default) – HBFDF835I-8365-V (CPU: I5-8365UE, Wifi) – HBFDF835-1021-V (CPU: I5-10210U) – HBFDF835I-1021-V (CPU: I5-10210U, Wifi)	
CPU/Chipset	– Intel® Whiskey Lake-U SoC Processor (TDP 15W) Notes : When the system runs, CPU will automatically adjust its working clock frequency according to changing workload.	
BIOS	– AMI Flash ROM	
Memory	– 2* DDR4 2400MHz SO-DIMM up to 64GB	
Network	– 1* Intel® i219LM GbE – 1* Intel® i225V 2.5GbE	

Graphics	<ul style="list-style-type: none"> - Intel® HD Graphics, shared memory - 1 * DP (Max Resolution: 4096x2304@60Hz) - 1 * HDMI 1.4 (Max Resolution: 4096x2160 @30Hz) - Support Dual Displays
Storage	<ul style="list-style-type: none"> - 1 * M.2 M-key (2242/2280, PCIe x4/SATA interface) support NVMe - 1 * 2.5" SATAIII Device (support 2.5" HDD with a height ≤ 10mm)
Expansion	<ul style="list-style-type: none"> - 1 * M.2 E-key (2230) support CNVi for WiFi expansion
Rear Panel I/O	<ul style="list-style-type: none"> - 4 * USB 3.1 (Gen.2) - 1 * USB 3.1 (Gen.2) Type C (USB data transfer only) - 1 * HDMI 1.4 (Max. resolution:4096 x 2160@30Hz) - 1 * DP (Max. resolution:4096 x 2304@60Hz) - 2 * RJ45 - 1 * Line-out - 1 * COM - 1 * DC-in jack
Front Panel I/O	<ul style="list-style-type: none"> - 1 * Power button - 1 * Reset button - 1 * Power LED - 1 * HDD LED - 2 * USB 2.0 - 1 * Line-out - 1 * MIC - 4 * COM
Internal Connector	<ul style="list-style-type: none"> - Onboard TPM2.0
Power Source	<ul style="list-style-type: none"> - MB: DC-in 9~24V - Adapter: AC_90~240V / DC12V / 90W
Compliance	<ul style="list-style-type: none"> - CE, FCC, LVD Ready
Dimensions	<ul style="list-style-type: none"> - System: 193 (W) x 142.4 (D) x 62 (H) mm - Box: 250 (W) x 118 (D) x 295 (H) mm
Temperature	<ul style="list-style-type: none"> - Operating Temperature: -20 ~ 60° C (Under the condition of using M.2 interface SSD) - Operating Temperature: 0 ~ 50° C (Under the condition of using 2.5" SATA HDD) (The test environment is closed and windless) - Storage Temperature: -40 ~ 85° C - Humidity: 10% ~ 95% RH @40°C (non-condensing)
OS Support	<ul style="list-style-type: none"> - Windows 10, Windows 11, Linux