

899.00 EUR
 incl. 19% VAT, plus [shipping](#)



- LGA1700 !
- 8x LAN !
- 2x COM !
- 12x LAN !



- Intel® LGA1700 supports 12th Gen. Core Processor
- 2* DDR5 4800MHz SO-DIMM up to 64GB
- 2* 2.5" SATA HDD device support RAID 0, 1, 5, 10
- 1* M.2 (M-key, 2242/2280), 1* M.2 (M-key, 2280), 1* M.2 (E-key), 1* M.2 (B-key), 1* PCIe4
- 12* 2.5GbE, 2* USB3.2 (Gen.2), 2* USB3.2 (Gen.1), 2* COM
- 1* HDMI
- ATX Power Input with 24pin ATX + 4pin 12V
- Support TPM2.0 (option)

Model	– HBJC153I23-Q670B (Default) – HBJC153I23-Q670G4 (Expansion PCIe 4* Lan Card) system total up to 12* LAN ports – HBJC153I23-Q670B4 (Expansion PCIe 4* Bypass Lan Card) system total up to 12* LAN ports
MB Model	– MI23-Q6700 (Q670E) – MI23-Q6702 (optional , Q670E,onboard TPM2.0)
CPU/Chipset	– Intel® 12th/13th LGA1700 Socket Core i7/i5/i3/Pentium/Celeron Processor(Max. 65W TDPs under 180A) – Intel® Q670E Chipset
BIOS	– AMI Flash ROM – Support recover crashed BIOS data tool by a USB flash pen driver: Using JetBIOS SW back up tool with any external USB ports
Memory	– 2* DDR5 4800MHz SO-DIMM up to 64GB
Network	– 7* Intel® i225-V 2.5GbE – 1* Intel® i225-LM 2.5GbE
Graphics	– Intel® UHD Graphics, shared memory – 1* HDMI (Max Resolution: 1920x1080@60Hz)
Storage	– 1* M.2 M-key (2242/2280, PCIe Gen.4x4 w/SATA interface) – 1* M.2 M-key (2280, PCIe Gen.4x4 w/SATA interface) support NVMe – 2* 2.5" SATA HDD device support RAID 0, 1 (support 2.5" HDD with a height 10mm)

Expansion	<ul style="list-style-type: none"> - 1* M.2 E-key (2230, USB2.0/PCIe x1) support CNVi - 1* M.2 B-key (3042, USB3.2 Gen.1/USB2.0/PCIe x1 interface) support 4G Module - 1* PCIe Gen.4x4 slot
Rear Panel I/O	<ul style="list-style-type: none"> - AC input CON - Power on/off SW
Front Panel I/O	<ul style="list-style-type: none"> - 8* RJ45 - 2* USB3.2 (Gen.2) - 2* USB3.2 (Gen.1) - 1* COM (RS232) (Not installed when leaving the factory, the wires are placed in the parts box) - 1* HDMI (Not installed when leaving the factory, the wires are placed in the parts box) - 1* Alarm LED, 1* Power LED - Power on/off SW
Internal Connector	<ul style="list-style-type: none"> - SIM Card Holder
Power Source	<ul style="list-style-type: none"> - Power : 1U FLEX 300W POWER - MB : ATX Power Input (24pin ATX + 4pin 12V)
Compliance	<ul style="list-style-type: none"> - CE, FCC, LVD, RoHS, ErP Ready
Dimensions	<ul style="list-style-type: none"> - System: 430 (W) x 252 (D) x 44(H) mm - Box: 560 (W) x 400 (D) x 380 (H) mm
Temperature	<ul style="list-style-type: none"> - Operating Temperature: 0 ~ 50° C - Storage Temperature: -40 ~ 85° C - Humidity: 10%~95% @40° C (non-condensing)
OS Support	<ul style="list-style-type: none"> - Windows 11, Linux