



69.00 EUR

incl. 19% VAT, plus [shipping](#)

- 4x USB on rear side !
- Mini-PCI
- Dual LAN
- Ideal for M2-ATX

- for Intel Core Duo / Core Single CPUs with 533/677 MHz FSB, Mobile Socket 479
- 2x 240-pin DIMM socket (DDR-II 533/677, up to 2GB)
- 1x 44-pin Standard-IDE Port
- 1x PCI-express
- 1x SATA
- 1x Mini-PCI
- 1x Gigabit LAN
- 1x 100Mbit LAN
- Graphics adapter onboard (Intel GMA 950)
- Sound onboard (Realtek ALC662)
- Standard 20pol-ATX power connector
- TV-Out (S-Video + RCA)

**Scope of supply :**

- I94GM-I4 Mainboard
- Slim CPU Coolermaster Alu cooler (27W CPU Max.)
- IDE-cable (40 to 44 pin)
- 1x SATA cable

Chipset: Intel 945GM / ICH7M

**CPU SUPPORT**

- Intel Core 2 Duo
- Intel Core Duo
- Intel Celeron M

**MEMORY**

- Support Dual DDR2 533/667 MHz 2 x DDR2 DIMM Memory Slot Max. Supports up to 2GB Memory

**EXPANSION SLOT**

- 1 x PCI-E Slot
- 1 x Mini-PCI Slot

**GRAPHICS**

Intel Graphics Media Accelerator 950, On Board Graphic Max. Share Memory Up To 224MB

**AUDIO**

Realtek ALC662 5.1-Channel HD Audio

**LAN**

1x Realtek 10/100/1000 Mbit RTL8111B

1x Realtek 10/100 Mbit RTL8101E

SUPER I/O CHIP  
ITE IT8718

REAR I/O

- 1 x PS/2 Mouse
- 1 x PS/2 Keyboard
- 4 x USB 2.0 Ports
- 1 x RS-232 Port
- 1 x D-Sub
- 1 x S-Video
- 1 x Composite Video
- 2 x LAN
- 3 x Audio jacks

INTERNAL I/O

- 1 x SATA Connector
- 1 x IDE 44 Pin, 2.0 Pitch
- 1 x USB 2.0 Header
- 1 x Serial Header
- 1 x SP/DIF OUT Header
- 1 x CD-IN Header
- 1 x Front Audio Header
- 1 x LVDS Connector
- 1 x YPbPr Header
- 1 x CIR Header
- 1 x Front Panel Header
- 1 x ATX Power Connector

OS SUPPORT

- Support Windows CE / 2000 / XP
- Support Linux

DIMENSION

170mm x 170mm ( W x L )

Reviews/Awards :

